

# Overview

I "enhanced" my Dell Precision T3400 with an additional graphic card and setup a raid 0 on 2 disks

Here's the output of lspci

```
00:00.0 Host bridge: Intel Corporation 82X38/X48 Express DRAM Controller
00:01.0 PCI bridge: Intel Corporation 82X38/X48 Express Host-Primary PCI
Express Bridge
00:06.0 PCI bridge: Intel Corporation 82X38/X48 Express Host-Secondary PCI
Express Bridge
00:1a.0 USB controller: Intel Corporation 82801I (ICH9 Family) USB UHCI
Controller #4 (rev 02)
00:1a.1 USB controller: Intel Corporation 82801I (ICH9 Family) USB UHCI
Controller #5 (rev 02)
00:1a.2 USB controller: Intel Corporation 82801I (ICH9 Family) USB UHCI
Controller #6 (rev 02)
00:1a.7 USB controller: Intel Corporation 82801I (ICH9 Family) USB2 EHCI
Controller #2 (rev 02)
00:1b.0 Audio device: Intel Corporation 82801I (ICH9 Family) HD Audio
Controller (rev 02)
00:1c.0 PCI bridge: Intel Corporation 82801I (ICH9 Family) PCI Express Port
1 (rev 02)
00:1c.5 PCI bridge: Intel Corporation 82801I (ICH9 Family) PCI Express Port
6 (rev 02)
00:1d.0 USB controller: Intel Corporation 82801I (ICH9 Family) USB UHCI
Controller #1 (rev 02)
00:1d.1 USB controller: Intel Corporation 82801I (ICH9 Family) USB UHCI
Controller #2 (rev 02)
00:1d.2 USB controller: Intel Corporation 82801I (ICH9 Family) USB UHCI
Controller #3 (rev 02)
00:1d.7 USB controller: Intel Corporation 82801I (ICH9 Family) USB2 EHCI
Controller #1 (rev 02)
00:1e.0 PCI bridge: Intel Corporation 82801 PCI Bridge (rev 92)
00:1f.0 ISA bridge: Intel Corporation 82801IR (ICH9R) LPC Interface
Controller (rev 02)
00:1f.2 RAID bus controller: Intel Corporation 82801 SATA Controller [RAID
mode] (rev 02)
00:1f.3 SMBus: Intel Corporation 82801I (ICH9 Family) SMBus Controller (rev
02)
01:00.0 VGA compatible controller: NVIDIA Corporation Device 11c0 (rev a1)
01:00.1 Audio device: NVIDIA Corporation Device 0e0b (rev a1)
02:00.0 VGA compatible controller: NVIDIA Corporation G80 [Quadro FX 4600]
(rev a2)
04:00.0 Ethernet controller: Broadcom Corporation NetXtreme BCM5754 Gigabit
Ethernet PCI Express (rev 02)
```


Here's the output of lsusb

```

Bus 001 Device 003: ID 05e3:0607 Genesys Logic, Inc. Logitech G110 Hub
Bus 001 Device 004: ID 0718:0146 Imation Corp.
Bus 003 Device 002: ID 06a3:0cd0 Saitek PLC
Bus 001 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub
Bus 002 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub
Bus 003 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub
Bus 004 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub
Bus 005 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub
Bus 006 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub
Bus 007 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub
Bus 008 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub
Bus 001 Device 005: ID 046d:c228 Logitech, Inc.
Bus 001 Device 006: ID 046d:c229 Logitech, Inc.

```

Here's the output of `cpuinfo`



## Partition table

Disk	Partition	Name	Label	Size	Format	Comment
raid0	Volume1p0	?	?	?	NTFS	C:\
raid0	Volume1p1	?	LINUX	?	ext4	/
raid0	Volume1p2	?	?	?	?	?
raid0	Volume1p3	?	?	?	?	?
raid0	Volume1p4	?	?	?	?	?
raid0	Volume1p5	?	SWAP	?	swap	swap
raid0	Volume1p6	?	HOME	?	ext4	/home partition

## Base install

### References

- [Installation guide](#)

### First install

Boot on the USB stick / CD - the isos are taken from here → <https://www.archlinux.org/download/> take the mirror closest to you and select the netinstall ISO

## boot

On Dell's BIOS you have to press [F12] to boot from a different device.



Since double wankers have time to spare to code drivers and oblige people to use it, you have to put "nomodeset" on the boot commandline otherwise nouveau will crash the boot! Sorry to have 2 graphic cards and 3 screens ...

## Basic

### Remote access

Let's launch the network + sshd so we can copy paste some nice commands right from an already installed machine

```
ip addr show
```

Start sshd

```
systemctl start sshd
```

I hate systemd right from this line ... !

Set a root password

```
passwd
```

## Raid

Reference: [https://wiki.archlinux.org/index.php/Installing\\_with\\_Fake\\_RAID](https://wiki.archlinux.org/index.php/Installing_with_Fake_RAID)

And yet another enhancement ... raid doesn't work by default anymore



```
ls -al /dev/mapper  
arch_root-image@ control
```

empty...

test

```
dmraid -r  
/dev/sdb: isw, "isw_dbdeeiaadjh", GROUP, ok, 976773165 sectors, data@ 0  
/dev/sda: isw, "isw_dbdeeiaadjh", GROUP, ok, 976773165 sectors, data@ 0
```

Recognized ...

Try to start it:

```
dmraid -ay
RAID set "isw_dbdeeiadjh_Volume0" was not activated
RAID set "isw_dbdeeiadjh_Volume1" was not activated
ERROR: device "isw_dbdeeiadjh_Volume0" could not be found
ERROR: device "isw_dbdeeiadjh_Volume1" could not be found
```

Perfect ...

Output of dmesg:

```
[ 209.459439] device-mapper: table: 254:1: striped: Couldn't parse stripe
destination
[ 209.459525] device-mapper: ioctl: error adding target to table
[ 209.459967] device-mapper: table: 254:1: striped: Couldn't parse stripe
destination
[ 209.460063] device-mapper: ioctl: error adding target to table
```

Impressive...

In order to make the raid work and be recognize:

```
ls -l /dev/md
total 0
lrwxrwxrwx 1 root root 8 May 29 10:39 imsm0 -> ../md127
lrwxrwxrwx 1 root root 8 May 29 10:39 Volume0_0 -> ../md125
lrwxrwxrwx 1 root root 10 May 29 10:39 Volume0_0p1 -> ../md125p1
lrwxrwxrwx 1 root root 10 May 29 10:39 Volume0_0p2 -> ../md125p2
lrwxrwxrwx 1 root root 8 May 29 10:39 Volume1_0 -> ../md126
lrwxrwxrwx 1 root root 10 May 29 10:39 Volume1_0p1 -> ../md126p1
lrwxrwxrwx 1 root root 10 May 29 10:39 Volume1_0p2 -> ../md126p2
lrwxrwxrwx 1 root root 10 May 29 10:39 Volume1_0p5 -> ../md126p5
lrwxrwxrwx 1 root root 10 May 29 10:39 Volume1_0p6 -> ../md126p6
```

You'll find all mdXXX device created by who knows what AND fucking up the fakeraid (why does my intuition turns to shit systemd???)

Stop this madness:

```
mdadm -S /dev/mdXXX
```

Replace XXX by the values ... in this example: md126/125/127 ...

Then suddenly

```
dmraid -ay
RAID set "isw_dbdeeiadjh_Volume0" was activated
RAID set "isw_dbdeeiadjh_Volume1" was activated
device "isw_dbdeeiadjh_Volume0" is now registered with dmeventd for
monitoring
device "isw_dbdeeiadjh_Volume1" is now registered with dmeventd for
monitoring
RAID set "isw_dbdeeiadjh_Volume0p1" was activated
RAID set "isw_dbdeeiadjh_Volume0p2" was activated
RAID set "isw_dbdeeiadjh_Volume1p1" was activated
```

```
RAID set "isw_dbdeeiadjh_Volume1p5" was activated
RAID set "isw_dbdeeiadjh_Volume1p6" was activated
```

Amazing! and GG!

## Formatting

Let's format all these partitions in ext4 format.

```
mkfs.ext4 -L LINUX /dev/mapper/isw_dbdeeiadjh_Volume1p1
mkfs.ext4 -L HOME /dev/mapper/isw_dbdeeiadjh_Volume1p6
mkswap -L SWAP /dev/mapper/isw_dbdeeiadjh_Volume1p5
```

## Mount them

Mounting and creating mount points:

```
mount /dev/mapper/isw_dbdeeiadjh_Volume1p1 /mnt
mkdir /mnt/home
mount /dev/mapper/isw_dbdeeiadjh_Volume1p6 /mnt/home
swapon /dev/mapper/isw_dbdeeiadjh_Volume1p5
```

Check

```
mount
```

## Base system

I'll then install base packages plus base-level packages

```
pacstrap /mnt base base-devel
```

## Fstab

- generate fstab

```
genfstab -L -p /mnt >> /mnt/etc/fstab
```

Yes I use Labels, UUID sucks

- check fstab

```
#
# /etc/fstab: static file system information
```

```
#
# <file system> <dir> <type> <options> <dump> <pass>
# /dev/mapper/isw_dbdeeiadjh_Volume1p1 UUID=2141c0d6-1804-4cb0-
ac76-661a6cad6f90
LABEL=LINUX / ext4
rw,relatime,stripe=64,data=ordered 0 1
[Fstab]
# /dev/mapper/isw_dbdeeiadjh_Volume1p6
UUID=b8a60d67-40da-41e6-94e9-28af9e55a592
LABEL=HOME /home ext4
rw,relatime,data=ordered 0 2
# /dev/mapper/isw_dbdeeiadjh_Volume1p5 UUID=369d66b4-d45a-4ded-
a29c-7817e2ece675
LABEL=SWAP none swap defaults 0 0
```

## Bootloader

I use Syslinux since it does its job well! [Syslinux](#)

```
pacstrap /mnt syslinux
```

# Configuration

## Environment

Let's go to our new system!

```
arch-chroot /mnt
```

- /etc/hostname

```
echo c3n0t4f > /etc/hostname
```

- /etc/locale.gen

I'll use en\_US.utf-8/iso8859 so uncomment:

```
en_US.UTF-8 UTF-8
en_US ISO-8859-1
```

The generate locales

```
locale-gen
```

- /etc/locale.conf [Locale](#)

```
LANG="en_US.UTF-8"
```

```
# Keep the default sort order (e.g. files starting with a '.'
# should appear at the start of a directory listing.)
LC_COLLATE="C"
```

- /etc/vconsole.conf

Default keyboard in console (US variant international ... with a different mapping than on X11! Well done)

```
echo "KEYMAP=us-acentos" > /etc/vconsole.conf
```

- /etc/localtime

```
ln -s /usr/share/zoneinfo/Europe/Paris /etc/localtime
```

- /etc/mkinitcpio.conf

Add:

```
[...]
MODULES="dm_mod"
[...]
HOOKS="base udev autodetect modconf block dmraid filesystems keyboard fsck"
```

reference: [https://wiki.archlinux.org/index.php/Installing\\_with\\_Fake\\_RAID#Install\\_and\\_configure\\_Arch](https://wiki.archlinux.org/index.php/Installing_with_Fake_RAID#Install_and_configure_Arch)  
Build the images ...

```
mkinitcpio -p linux
```

- /boot/syslinux/syslinux.cfg

Changed sda3 by the almighty name of the raid ... + uncommented windows part

Then the magic:

```
/usr/sbin/syslinux-install_update -i -a -m
```

I get some funny nice message:

```
Syslinux install successful
Boot Flag Set - /dev/mapper/isw_dbdeeidjh_Volume1p1
ABORT! MBR installation to partition (/dev/mapper/isw_dbdeeidjh_Volume1)!
```

Successful and ABORT at the same time! GG again!

- root password

```
passwd
```

# Reboot

## Umount stuff cleanly

First use Ctrl+D to escape from the chroot then:

```
umount /mnt/var /mnt/home /mnt
```

Now is the time to light a candle and type

```
reboot
```

## Pimping up shit created by systemd

So, happily you used to refer to your network card as eth0? Forget it! Now huge brains have decided for you, even if you don't have any issue that the notation will change! Great ... so my eth0 is called ... wait for it: enp0s25 perfect. So let's remove that shit! (wlan0 is called wlp3s0 by the way - unfortunately, so far they didn't change the lo interface \o/ it's called ... lo ... what a lack of imagination!!)

```
ln -s /dev/null /etc/udev/rules.d/80-net-name-slot.rules
```

Reboot! Yeah you know just like on Windows©

# Network

## Dhcpd for eth 0

Once you have back a proper name for you interfaces ...

```
systemctl enable dhcpd@eth0
```

And then it slows down your boot! Isn't that nice? Well coded.  
Reference: [Network](#)

## Netctl for wifi

Reference: <https://wiki.archlinux.org/index.php/Netctl>

```
pacman -S netctl wpa_supplicant
```

```
cd /etc/netctl/examples/
```

Copy on of the example regarding the type of network you want to access:

```
cp wireless-wpa-configsection ../university
```

Edit the file with proper settings (SSID / user ... )

```
cd /etc/netctl
vi university
```

I don't use auto-wifi service I start it when needed:

```
netctl start university
```

## SSHD

Access remotely:

```
pacman -Sy openssh
```

Enable it at boot

## User

```
useradd -g users -m -s /bin/bash warnaud
passwd warnaud
```

## Fix VI/VIM

```
# ls -altrh `which vi`
lrwxrwxrwx 1 root root 2 Nov 16 18:34 /usr/bin/vi -> ex
```

Prefer vim?

```
pacman -S vim
rm /usr/bin/vi && ln -s /usr/bin/vim /usr/bin/vi
```

## GPM

Since gpm is a dependency of vim let's use it!

```
systemctl enable gpm
systemctl start gpm
```

# Xorg / XDM

## Xorg

Reference: [Xorg](#) & [Intel](#) Install all those packages ...

```
# pacman -S xorg-server xorg-apps xorg-fonts xorg-fonts-100dpi xorg-
fonts-75dpi xorg-twm xorg-xclock xorg-xinit xorg-xdm xterm xf86-video-intel
xorg-xmessage xorg-xcalc xorg-xfontsel xorg-utils
```

Reply to questions:

```
:: There are 37 members in group xorg-apps:
:: Repository extra
 1) xorg-bdftopcf  2) xorg-iceauth  3) xorg-luit  4) xorg-mkfontdir  5)
xorg-mkfontscale  6) xorg-sessreg  7) xorg-setxkbmap  8) xorg-smproxy
 9) xorg-x11perf 10) xorg-xauth  11) xorg-xbacklight 12) xorg-xcmsdb
13) xorg-xcursorgen 14) xorg-xdpyinfo 15) xorg-xdriinfo 16) xorg-xev
 17) xorg-xgamma 18) xorg-xhost 19) xorg-xinput 20) xorg-xkbcomp 21)
xorg-xkbevd 22) xorg-xkbutils 23) xorg-xkill 24) xorg-xlsatoms
 25) xorg-xlsclients 26) xorg-xmodmap 27) xorg-xpr 28) xorg-xprop 29)
xorg-xrandr 30) xorg-xrdb 31) xorg-xrefresh 32) xorg-xset 33) xorg-
xsetroot
 34) xorg-xvinfo 35) xorg-xwd 36) xorg-xwininfo 37) xorg-xwud
```

Enter a selection (default=all):

```
:: There are 2 members in group xorg-fonts:
:: Repository extra
 1) xorg-font-util 2) xorg-fonts-encodings
```

Enter a selection (default=all): 1

resolving dependencies...

```
:: There are 4 providers available for libgl:
```

```
:: Repository extra
 1) mesa-libgl 2) nvidia-304xx-utils 3) nvidia-libgl
:: Repository community
 4) catalyst-utils
```

Enter a number (default=1): 1

Add some modules at boot for KMS

```
vi /etc/mkinitcpio.conf
```

```
...
MODULES="i915"
...
```

Acceleration method

```
vi /etc/X11/xorg.conf.d/20-intel.conf
```

```
Section "Device"
    Identifier "Intel Graphics"
    Driver     "intel"
    Option     "AccelMethod"  "sna"
EndSection
```

```
vi /etc/X11/xorg.conf.d/10-evdev.conf
```

```
Section "InputClass"
    Identifier "evdev keyboard catchall"
    MatchIsKeyboard "on"
    MatchDevicePath "/dev/input/event*"
    Driver "evdev"
    Option "XkbLayout" "us"
    Option "XkbVariant" "intl"
EndSection
```

## XDM

Reference: <https://wiki.archlinux.org/index.php/XDM>

```
pacman -S xorg-xdm
```

Enable systemd service

```
systemctl enable xdm.service
```

Optional, if you made a customize version

```
vi /usr/lib/systemd/system/xdm.service
```

```
[Unit]
Description=X-Window Display Manager
After=systemd-user-sessions.service

[Service]
ExecStart=/usr/bin/xdm -c /etc/X11/xdm/lcars-xdm/xdm-config -nodaemon
Type=notify
NotifyAccess=all

[Install]
Alias=display-manager.service
```

Copy the necessary files from /etc/skel

```
cp /etc/skel/.xsession ~/.
```

make sure its permission are 774

## Fvwm

```
pacman -S fvwm
```

Import my configuration:

```
mkdir ~/.fvwm && cd .fvwm && svn co  
https://fvwm.svn.beanstalkapp.com/fvwm/trunk/bazooka .
```

## Alsa

Reference: <https://wiki.archlinux.org/index.php/Alsa>

```
pacman -S alsa-utils
```

Set volume levels:

```
alsamixer
```

Test:

```
speaker-test -c 2
```

## Laptop / powersaving (doesn't work ... )

Reference: <https://wiki.archlinux.org/index.php/Laptop>

## ACPID

To have access to buttons + power settings, first install acpi and acpid

```
pacman -S acpi acpid
```

Reference: <https://wiki.archlinux.org/index.php/Acpi> and <https://wiki.archlinux.org/index.php/Acpid> and [https://wiki.archlinux.org/index.php/ACPI\\_hotkeys](https://wiki.archlinux.org/index.php/ACPI_hotkeys) Start the daemon and enable it:

```
systemctl enable acpid
```

```
systemctl start acpid
```

## TPB

For other nice osd display install tpb



:

```
yaourt -S tpb
```

Reference:[https://wiki.archlinux.org/index.php/ThinkPad\\_OSD](https://wiki.archlinux.org/index.php/ThinkPad_OSD) Configure it:

```
vi /etc/tpbrc
```

```
OSDCOLOR      Green
OSDVERTICAL   0
OSDHORIZONTAL 0
OSDPOS        MIDDLE
OSDALIGN      CENTER
```

## Udev

Create a special rule to suspend everything if battery is at 2%

```
vi /etc/udev/rules.d/lowbat.rules
```

```
## SLEEP IF BATTERY IS LOW
SUBSYSTEM=="power_supply", ATTR{status}=="Discharging", ATTR{capacity}=="2",
RUN+="/usr/bin/systemctl suspend"
```

## i915

Power consumption for Intel Graphics:

```
vi /etc/modprobe.d/modprobe.conf
```

```
options i915 i915_enable_rc6=1 i915_enable_fbc=1 lvds_downclock=1
```

Rebuild the kernel:

```
mkinitcpio -p linux && mkinitcpio -p linux-ck
```

## TLP

Reference:<https://wiki.archlinux.org/index.php/TLP> Install required packages:

```
yaourt -S tlp tp_smapi tp_smapi-ck dkms-acpi_call-git smartmontools
```



tp\_smapi doesn't seem to launch ... Enable the service:

```
systemctl enable tlp
```

## Sysctl



Reference: <https://wiki.archlinux.org/index.php/Sysctl> add in /etc/sysctl.conf

```
vm.dirty_writeback_centisecs=1500  
vm.laptop_mode=5
```

## Syslinux

After those tweaks, here's Syslinux cfg file

```
DEFAULT arch-ck  
PROMPT 0          # Set to 1 if you always want to display the boot: prompt  
TIMEOUT 50  
  
UI vesamenu.c32  
  
MENU RESOLUTION 1366 768  
MENU CLEAR  
  
MENU TITLE ~ 30L3 - Select OS ~  
MENU COLOR border      30;44   #40ffffff #a0000000 std  
MENU COLOR title       1;36;44 #9033ccff #a0000000 std  
MENU COLOR sel         7;37;40 #e0ffffff #20ffffff all  
MENU COLOR unsel       37;44   #50ffffff #a0000000 std  
MENU COLOR help        37;40   #c0ffffff #a0000000 std  
MENU COLOR timeout_msg 37;40   #80ffffff #00000000 std  
MENU COLOR timeout     1;37;40 #c0ffffff #00000000 std  
MENU COLOR msg07       37;40   #90ffffff #a0000000 std  
MENU COLOR tabmsg      31;40   #30ffffff #00000000 std  
  
LABEL arch  
    MENU LABEL Arch Linux  
    LINUX ../vmlinuz-linux  
    APPEND root=/dev/sdb3 ro  
    INITRD ../initramfs-linux.img quiet vga=current ipv6.disable=1  
    pcie_aspm=force acpi_backlight=vendor  
  
LABEL archfallback  
    MENU LABEL Arch Linux Fallback
```

```
LINUX ../vmlinuz-linux
APPEND root=/dev/sdb3 ro
INITRD ../initramfs-linux-fallback.img

LABEL arch-ck
  MENU LABEL Arch Linux CK
  LINUX ../vmlinuz-linux-ck
  APPEND root=/dev/sdb3 ro
  INITRD ../initramfs-linux-ck.img quiet vga=current ipv6.disable=1
elevator=bfq pcie_aspm=force acpi_backlight=vendor

LABEL arch-ck-fallback
  MENU LABEL Arch Linux CK Fallback
  LINUX ../vmlinuz-linux-ck
  APPEND root=/dev/sdb3 ro
  INITRD ../initramfs-linux-ck-fallback.img

LABEL windows
  MENU LABEL Windows 7 Professional 64bits
  COM32 chain.c32
  APPEND hd0 1

LABEL hdt
  MENU LABEL HDT (Hardware Detection Tool)
  COM32 hdt.c32

LABEL reboot
  MENU LABEL Reboot
  COM32 reboot.c32

LABEL off
  MENU LABEL Power Off
  COMBOOT poweroff.com
```

## Thinkpad

### Wacom

Reference: <https://wiki.archlinux.org/index.php/Wacom> Install the driver:

```
pacman -S xf86-input-wacom
```



la suite ...

### Disable Touchpad

Deactivate the useless touchpad:

```
vi /etc/X11/xorg.conf.d/10-evdev.conf
```

```
Section "InputClass"
    Identifier "evdev touchpad catchall"
    MatchIsTouchpad "off"
    MatchDevicePath "/dev/input/event*"
    Driver "evdev"
EndSection
```



**Fix Me!**

Check alternate

solution: [https://wiki.archlinux.org/index.php/Synaptics\\_Touchpad](https://wiki.archlinux.org/index.php/Synaptics_Touchpad)

## TrackNav enhancement

This hack will enable scrolling using the middle button + the TrackPoint™ ® ©

```
vi /etc/X11/xorg.conf.d/20-thinkpad.conf
```

```
Section "InputClass"
    Identifier "Trackpoint Wheel Emulation"
    MatchProduct "TPPS/2 IBM TrackPoint|DualPoint Stick|Synaptics
Inc. Composite TouchPad / TrackPoint|ThinkPad USB Keyboard with
TrackPoint|USB Trackpoint pointing device"
    MatchDevicePath "/dev/input/event*"
    Option "EmulateWheel" "true"
    Option "EmulateWheelButton" "2"
    Option "Emulate3Buttons" "false"
    Option "XAxisMapping" "6 7"
    Option "YAxisMapping" "4 5"
EndSection
```

## Fingerprint reader

Reference: <https://wiki.archlinux.org/index.php/Fingerprint-gui> Unfortunately no free software for my fingerprint reader I have to use fingerprint-gui, anyhow it works!

```
yaourt -S fingerprint-gui
```

Sadly it depends on tons of crap like Qt ...  
Add you user(s) to the plugdev group

```
sudo gpasswd -a USERNAME plugdev
```

Configure applications to recognize fingerprints:

- sudo

**vi** /etc/pam.d/sudo

```

#%PAM-1.0
auth          sufficient      pam_fingerprint-gui.so
auth          required        pam_unix.so
auth          required        pam_nologin.so

```



- su (doesn't work for me ... )

**vi** /etc/pam.d/su

```

#%PAM-1.0
auth          sufficient      pam_rootok.so
auth          sufficient      pam_fingerprint-gui.so
# Uncomment the following line to implicitly trust users in the "wheel"
group.
#auth         sufficient      pam_wheel.so trust use_uid
# Uncomment the following line to require a user to be in the "wheel" group.
#auth         required        pam_wheel.so use_uid
auth          required        pam_unix.so
account       required        pam_unix.so
session       required        pam_unix.so

```

- xscreensaver

**vi** /etc/pam.d/xscreensaver

```

auth          sufficient      pam_fingerprint-gui.so
auth          required        pam_unix_auth.so

```

- xdm

**vi** /etc/pam.d/xdm

```

#%PAM-1.0
auth          sufficient      pam_fingerprint-gui.so
auth          required        pam_unix.so
auth          required        pam_nologin.so
auth          required        pam_env.so
account       required        pam_unix.so
password      required        pam_unix.so
session       required        pam_unix.so
session       required        pam_limits.so
session       required        pam_loginuid.so
-session      optional        pam_systemd.so

```

Register your fingerprints



In an X environment



Might need a reboot to load the appropriate modules ...



```
fingerprint-gui
```

The interface is pretty self explanatory. You have to select the device first then scan the fingers you want.

If in the drop down menu you have Unknown device, reboot (or find the nice corresponding module) ===== Bluetooth ===== Level 3 Headline Reference: <https://wiki.archlinux.org/index.php/Bluetooth>

```
pacman -S bluez
```



**Fix Me!**

Any of this required?

Optional dependencies for bluez

```
gstreamer0.10-base: bluetooth GStreamer support
alsa-lib: Audio bluetooth devices support [installed]
dbus-python: to run bluez-simple-agent
pygobject: to run bluez-simple-agent
libusb-compat: USB adapters support
cups: CUPS backend
```

I kind of never use bluetooth so I start it when necessary

```
systemctl start bluetooth.service
```



**Fix Me!**

.. have some fun with it

## Multimedia Keys

Mute/Volume up and Down are recognized by default in xev, so with xbindkeys let's map them

```
pacman -S xbindkeys
```

Create a file that contain the definition of the buttons + the action(s)

```
vi ~/.xbindkeysrc.scn
```

Here I'll map Mute / Volume up / Volume Down

```
(xbindkey '("XF86AudioMute") "amixer set Master toggle")
(xbindkey '("XF86AudioRaiseVolume") "amixer set Master 2dB+ unmute")
(xbindkey '("XF86AudioLowerVolume") "amixer set Master 2dB- unmute")
```

Last but not least, add

```
xbindkeys &
```

To your ~/.xinitrc or whatever file launched at login

## Systemd journal

It's always nice to see some logs even if they are in binary format .....

```
Hint: You are currently not seeing messages from other users and the system.
      Users in the 'systemd-journal' group can see all messages. Pass -q to
      turn off this notice.
```

Fix:

```
sudo gpasswd -a USERNAME systemd-journal
```

## Other software

### Archlinuxfr repository

```
vi /etc/pacman.conf
```

```
...
[archlinuxfr]
SigLevel = Never
Server = http://repo.archlinux.fr/$arch
```

\o/ No signature

### Yaourt

Reference: <http://archlinux.fr/yaourt-en>

```
pacman -Sy yaourt
```

### Sudo

```
pacman -S sudo
```

```
visudo
```

```
...
```

```
root ALL=(ALL) ALL
someuser ALL=(ALL) ALL
```

Just add the 'someuser' line

## Compilation options



just for fun not really mandatory Reference: <https://wiki.archlinux.org/index.php/Makepkg.conf>

```
vi /etc/makepkg.conf
```

Modify CFLAGS/CXXFLAGS:

```
# -march=native also sets the correct -mtune=
CFLAGS="-march=native -O2 -pipe -fstack-protector --param=ssp-buffer-size=4
-D_FORTIFY_SOURCE=2"
CXXFLAGS="${CFLAGS}"
```

Modify MAKEFLAGS (4 = output of nproc)

```
MAKEFLAGS="-j4"
```

## Mandatory packages - for terminal users

List of software I use and abuse

```
yaourt -S screen bash-completion wavemon glances htop bmon irssi lftp rsync
wget curl bc figlet toilet pmount dfc git rdesktop
```

I use yaourt since some of them are not in repositories and then built from aur

## Cups

Reference: <https://wiki.archlinux.org/index.php/Cups>

```
pacman -S libcups cups cups-filters ghostscript gsfonts
```

## CK Kernel

For more aggressive scheduling, you can use the ck patchset

References:

- <https://wiki.archlinux.org/index.php/Kernel26-ck>
- <https://wiki.archlinux.org/index.php/Repo-ck>



Super up-to-date



```
vi /etc/pacman.conf
```

Add at the end:

```
[repo-ck]
SigLevel = PackageRequired
Server = http://repo-ck.com/$arch
```

Add keys for signing shit ...

```
pacman-key -r 5EE46C4C
pacman-key --lsign-key 5EE46C4C
```

Refresh pacman's database:

```
pacman -Sy
```

Install kernel-ck matching your architecture (see Repo-ck page for reference)

```
pacman -S linux-ck-ivybridge linux-ck-ivybridge-headers
```

Add a nice entry in syslinux

```
vi /boot/syslinux/syslinux.cfg
```

```
...
DEFAULT arch-ck
...
LABEL arch-ck
    MENU LABEL Arch Linux CK
    LINUX ../vmlinuz-linux-ck
    APPEND root=/dev/sdb3 ro
    INITRD ../initramfs-linux-ck.img quiet ipv6.disable=1 elevator=bfq

LABEL arch-ck-fallback
    MENU LABEL Arch Linux CK Fallback
    LINUX ../vmlinuz-linux-ck
    APPEND root=/dev/sdb3 ro
    INITRD ../initramfs-linux-ck-fallback.img
...
```

Bye bye IPv6 and change the schedule to Con Kolivas' bfq

## URxvt

```
pacman -S rxvt-unicode urxvt-perls
```

(Not yet implemented : )

```
URxvt.perl-ext-common:      default,clipboard,url-select,keyboard-select
URxvt.url-select.launcher:  chromium
URxvt.url-select.underline: true
URxvt.keysym.M-u:          perl:url-select:select_next
URxvt.keysym.M-Escape:    perl:keyboard-select:activate
URxvt.keysym.M-s:         perl:keyboard-select:search
```

## X11 software

```
yaourt -S chromium hsetroot imagemagick vlc emelfm2 flashplugin xosd
```

For acrobat reader/skype, there's a need for the multilib repository ... well coded too!

```
vi /etc/pacman.conf
```

Uncomment:

```
[multilib]
Include = /etc/pacman.d/mirrorlist
```

Then:

```
yaourt -Sy acroread skype
```



tons of 32bits libraries ....



acroread libre-office\* fonts skype...

## Final stuff

<https://wiki.archlinux.org/index.php/Readahead>

## Ntfs share

Reference: <https://wiki.archlinux.org/index.php/Ntfs>

```
pacman -S ntfs-3g
```

```
vi /etc/fstab
```

```
#
# /etc/fstab: static file system information
```

```
#
# <file system> <dir> <type> <options> <dump> <pass>
# /dev/sdb3 UUID=34cedc78-e156-4dbb-a428-4d594d6b34a8
LABEL=LINUX / ext4
defaults,noatime,discard 0 1

# /dev/sda2 UUID=f8a1e862-64b7-41d7-ac7d-4b75b346ceb5
LABEL=VAR /var ext4
rw,relatime,data=ordered 0 2

# /dev/sda3 UUID=57552366-9356-43bf-8bd2-bb0b25a1d318
LABEL=HOME /home ext4
rw,relatime,data=ordered 0 2

# /dev/sda1 UUID=dcba8ead-fb4b-4e06-a9e5-1a55f1c353e0
LABEL=SWAP none swap defaults
0 0

# /dev/sda4 Windows
LABEL=DATA /media/data ntfs-3g
uid=warnaud,gid=users 0 0
```

## LibreOffice

Imagine Office in Java? There you go ...

Reference: <https://wiki.archlinux.org/index.php/LibreOffice>

```
yaourt -S ttf-dejavu artwiz-fonts libreoffice libreoffice-en-US libreoffice-
fr
```

Free to install ~70 pkgs \o/

## NTP

Reference: <https://wiki.archlinux.org/index.php/Ntp>

```
pacman -S ntp
```

```
vi /etc/ntp.conf
```

```
server 0.fr.pool.ntp.org iburst
server 1.fr.pool.ntp.org iburst
server 2.fr.pool.ntp.org iburst
server 3.fr.pool.ntp.org iburst
```

```
systemctl start ntpd
```

Well I don't enable it since ... I mostly have no connection at boot on a laptop 😊

From:  
<https://wiki.fortier-family.com/> - **Warnaud's Wiki**

Permanent link:  
<https://wiki.fortier-family.com/os/archlinux/c3n0t4f>

Last update: **2021/12/29 20:00**

