```
#List of valid properties:
# align
# color
# command
# full_text
# instance
# interval
# label
# min_width
# name
# separator
# separator_block_width
# short_text
# signal
# urgent

# Global properties
#
# The top properties below are applied to every block, but can be
overridden.
# Each block command defaults to the script name to avoid boilerplate.
command=/usr/share/i3blocks/$BLOCK_NAME
separator_block_width=15
markup=none


#[volume]
#label=VOL
#label=♪
#instance=Master
#instance=PCM
#interval=1
#signal=10

[disk]
#label=HOME
label=
#instance=/mnt/data
interval=30
separator=false

[wifi]
label=
instance=wlan0
interval=10
separator=false

[bandwidth]
instance=wlan0
interval=5
```

```
separator=false

[cpu_usage]
label=
interval=10
min_width=CPU: 100.00%
separator=false

[load_average]
interval=10
separator=false

[battery]
#label=BAT
label=⚡
#instance=1
interval=30
separator=false

[time]
command=date '+  %H:%M:%S    %d-%m-%Y'
interval=1

#[mediaplayer]
#label=
#instance=
#interval=1
#signal=1
```

From:
https://wiki.fortier-family.com/ - **Warnaud's Wiki**

Permanent link:
https://wiki.fortier-family.com/wm/i3/scripts/per-johan_halsli

Last update: **2021/12/29 21:09**